

BP880透過率

波長 (nm)	透過率 (%)
1100	14.25
1090	14.87
1080	15.75
1070	16.81
1060	18.12
1050	19.74
1040	21.72
1030	24.19
1020	27.27
1010	30.97
1000	35.45
990	40.73
980	47.00
970	54.19
960	61.90

波長 (nm)	透過率 (%)
950	70.04
940	78.29
930	85.87
920	91.19
910	94.94
900	97.21
890	97.99
880	97.30
870	95.13
860	91.47
850	83.73
840	67.51
830	41.96
820	17.15
810	4.09

波長 (nm)	透過率 (%)
800	0.66
790	0.09
780	0.02
770	0.01
760	0.00
750	0.00
740	0.00
730	0.00
720	0.00
710	0.00
700	0.00
690	0.00
680	0.00
670	0.00
660	0.00

波長 (nm)	透過率 (%)
650	0.00
640	0.00
630	0.00
620	0.00
610	0.00
600	0.00
590	0.00
580	0.00
570	0.00
560	0.00
550	0.00
540	0.00
530	0.00
520	0.00
510	0.00

波長 (nm)	透過率 (%)
500	0.00
490	0.00
480	0.00
470	0.00
460	0.00
450	0.00
440	0.00
430	0.00
420	0.00
410	0.00
400	0.00
390	0.00
380	0.00
370	0.00
360	0.00
350	0.00