

LP190透過率

波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)
2300	86.63	2010	87.27	1720	87.60	1430	87.38	1140	87.03	850	85.99	570	85.59
2290	86.68	2000	87.28	1710	87.61	1420	87.37	1130	86.97	840	86.00	560	85.51
2280	86.72	1990	87.29	1700	87.62	1410	87.36	1120	86.94	830	85.94	550	85.54
2270	86.76	1980	87.30	1690	87.63	1400	87.36	1110	86.98	820	86.04	540	85.55
2260	86.78	1970	87.31	1680	87.64	1390	87.31	1100	87.01	810	85.86	530	85.56
2250	86.82	1960	87.32	1670	87.68	1380	87.32	1090	86.96	800	85.93	520	85.65
2240	86.85	1950	87.32	1660	87.72	1370	87.23	1080	86.90	790	85.71	510	85.46
2230	86.89	1940	87.34	1650	87.83	1360	87.22	1070	86.90	780	85.99	500	85.46
2220	86.92	1930	87.34	1640	87.69	1350	87.33	1060	86.80	770	85.68	490	85.52
2210	86.93	1920	87.36	1630	87.64	1340	87.40	1050	86.78	760	85.74	480	85.38
2200	86.96	1910	87.36	1620	87.58	1330	87.34	1040	86.76	750	85.73	470	85.37
2190	86.98	1900	87.37	1610	87.56	1320	87.31	1030	86.74	740	85.97	460	85.34
2180	86.98	1890	87.38	1600	87.63	1310	87.28	1020	86.85	730	85.94	450	85.34
2170	87.01	1880	87.39	1590	87.65	1300	87.27	1010	86.74	720	85.87	440	85.41
2160	87.03	1870	87.41	1580	87.57	1290	87.28	1000	86.69	710	85.80	430	85.27
2150	87.04	1860	87.43	1570	87.57	1280	87.30	990	86.55	700	85.73	420	85.21
2140	87.08	1850	87.45	1560	87.47	1270	87.24	980	86.64	690	85.59	410	85.05
2130	87.10	1840	87.47	1550	87.49	1260	87.23	970	86.52	680	85.93	400	85.14
2120	87.11	1830	87.49	1540	87.58	1250	87.20	960	86.62	670	85.78	390	85.02
2110	87.12	1820	87.50	1530	87.51	1240	87.18	950	86.54	660	85.71	380	84.92
2100	87.13	1810	87.51	1520	87.52	1230	87.19	940	86.30	650	85.80	370	84.96
2090	87.15	1800	87.52	1510	87.56	1220	87.18	930	86.57	640	85.74	360	85.16
2080	87.17	1790	87.53	1500	87.52	1210	87.12	920	86.36	630	85.76	350	84.81
2070	87.18	1780	87.54	1490	87.57	1200	87.11	910	85.97	620	85.76	340	84.79
2060	87.20	1770	87.55	1480	87.46	1190	87.10	900	86.02	610	85.65	330	84.71
2050	87.22	1760	87.56	1470	87.53	1180	87.14	890	86.82	600	85.66	320	84.56
2040	87.24	1750	87.57	1460	87.46	1170	87.13	880	85.97	590	85.59	310	84.60
2030	87.25	1740	87.58	1450	87.44	1160	87.07	870	85.75	580	85.61	300	84.09
2020	87.27	1730	87.59	1440	87.37	1150	87.07	860	85.46				