

LP418透過率

波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)	波長 (nm)	透過率 (%)
200	0.01	500	98.55	800	89.63	1100	76.29	1400	72.01	1700	73.57	2000	74.58
210	0.00	510	98.54	810	89.00	1110	76.06	1410	71.79	1710	73.71	2010	75.01
220	0.00	520	98.50	820	88.34	1120	75.83	1420	71.89	1720	73.81	2020	74.89
230	0.00	530	98.35	830	87.72	1130	75.62	1430	72.13	1730	73.86	2030	74.35
240	0.00	540	98.33	840	87.07	1140	75.44	1440	72.30	1740	73.87	2040	74.95
250	0.00	550	98.16	850	86.56	1150	75.25	1450	72.44	1750	73.96	2050	75.07
260	0.00	560	98.08	860	85.82	1160	75.08	1460	72.57	1760	73.94	2060	75.38
270	0.00	570	97.93	870	85.17	1170	74.93	1470	72.64	1770	73.86	2070	75.55
280	0.00	580	97.79	880	84.81	1180	74.77	1480	72.72	1780	74.08	2080	75.36
290	0.00	590	97.64	890	84.36	1190	74.63	1490	72.72	1790	73.99	2090	75.81
300	0.00	600	97.47	900	83.74	1200	74.51	1500	72.72	1800	74.25	2100	74.68
310	0.00	610	97.46	910	83.11	1210	74.36	1510	72.70	1810	74.12	2110	75.05
320	0.00	620	97.33	920	82.66	1220	74.25	1520	72.66	1820	74.12	2120	74.59
330	0.00	630	97.22	930	82.20	1230	74.12	1530	72.68	1830	74.26	2130	74.17
340	0.00	640	96.96	940	81.67	1240	74.00	1540	72.70	1840	74.08	2140	74.14
350	0.00	650	96.81	950	81.24	1250	73.91	1550	72.72	1850	74.22	2150	74.10
360	0.00	660	96.59	960	80.80	1260	73.84	1560	72.81	1860	74.60	2160	73.32
370	0.00	670	96.27	970	80.33	1270	73.77	1570	72.85	1870	74.16	2170	73.40
380	0.00	680	95.86	980	79.97	1280	73.71	1580	72.95	1880	74.42	2180	73.38
390	0.00	690	95.54	990	79.56	1290	73.65	1590	73.02	1890	74.38	2190	73.06
400	0.00	700	95.08	1000	79.21	1300	73.56	1600	73.10	1900	74.65	2200	72.32
410	8.04	710	94.73	1010	78.86	1310	73.49	1610	73.19	1910	74.29	2210	73.88
420	81.80	720	94.15	1020	78.53	1320	73.45	1620	73.30	1920	74.47	2220	73.22
430	97.41	730	93.67	1030	78.21	1330	73.41	1630	73.38	1930	74.61	2230	74.31
440	97.62	740	93.01	1040	77.88	1340	73.36	1640	73.44	1940	74.54	2240	73.77
450	97.59	750	92.72	1050	77.59	1350	73.25	1650	73.40	1950	74.53	2250	73.93
460	98.02	760	92.12	1060	77.29	1360	73.01	1660	73.33	1960	74.29	2260	74.45
470	98.12	770	91.48	1070	77.03	1370	73.01	1670	73.39	1970	74.40	2270	74.00
480	98.26	780	90.68	1080	76.76	1380	72.90	1680	73.58	1980	74.27	2280	74.01
490	98.32	790	90.02	1090	76.53	1390	72.44	1690	73.51	1990	74.90	2290	74.75
												2300	74.90